

LUKOIL GENESIS SPECIAL C3 5W-30

low-ash, synthetic engine oil for gasoline and diesel engines with DPF

APPROVALS

BMW LL-04
GM dexos 2™
MB 229.51/ 229.52*
VW 502 00 / 505 00 / 505 01

* approval pending

MEETS REQUIREMENTS

ACEA C3
API SN/CF
Fiat 9.55535 – S2
Ford WSS-M2C917-A
suitable also for **ACEA A3/B4** or **ACEA C2**

PRODUCT DESCRIPTION

LUKOIL GENESIS SPECIAL C3 5W-30 is a low-ash, synthetic engine oil for up-to-date gasoline and diesel engines with particulate filter. It offers high reliability and allows maximum reduction of fuel consumption. The new midSAPS technology protects the environment as well as the particulate filter because of the low content of sulphated ash, phosphor and sulphur.

LUKOIL GENESIS SPECIAL C3 5W-30 minimized oil related emissions and guarantees maximum protection of the environment.

LUKOIL GENESIS SPECIAL C3 5W-30 reduced ash formula provide Long durability of particulate filter.

LUKOIL GENESIS SPECIAL C3 5W-30 latest additive technology keeps engine clean, reduces friction and guarantees maximum engine lifetime.

LUKOIL GENESIS SPECIAL C3 5W-30 provide long oil drain intervals and thereby high economy.

APPLICATION

LUKOIL GENESIS SPECIAL C3 5W-30 can be used in many newer passenger cars, gasoline and diesel engines with DPF, especially for BMW, Mercedes Benz, Opel and Volkswagen.

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL GENESIS SPECIAL C3 5W-30
Density/15°C	kg/m ³	DIN 51575	849
Flash point COC	°C	ISO 2592	230
Viscosity class	SAE		5W-30
Viscosity/40°C	mm ² /s	DIN 51562/T1	68.9
Viscosity/100°C	mm ² /s	DIN 51562/T1	11.7
Viscosity index	---	DIN ISO 2909	166
Pour point	°C	DIN ISO 3016	<-39

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"